



# CO<sub>2</sub> LEAK DETECTOR SAN-13

The SAN-13 CO<sub>2</sub> Leak Detector is designed for employees or workers to detect areas in which CO<sub>2</sub> leaks can occur. It is highly sensitive, tracking even the smallest of CO<sub>2</sub> leaks.

## FEATURES

- Audible and visual indicator
- NDIR Sensor technology
  - takes 20 readings per second
- Rugged design with protective rubber enclosure
- Heavy duty metal clip
- Rechargeable Li-Ion battery
  - 12+ hours per charge
- Large OLED Display
- IP54 housing protects against dust and rain

## SPECIFICATIONS

- **Measurement Range:** 0-20% CO<sub>2</sub>
- **Sensor Accuracy:** ±70ppm  
±20% reading value
- **CO<sub>2</sub> Measurement Interval:** 20 readings per second
- **Audible Alarm:** 90 dB @ 10 cm
- **Sensor Life Expectancy:** 15 years

## INCLUDES

- 110/240 VAC USB Wall Adapter
- USB Cable for Charging
- User Manual

## ADDITIONAL PERSONAL DEVICES

- SAN-10 - Personal 5% CO<sub>2</sub> Safety Monitor
- SAN-20 - Personal O<sub>2</sub> Safety Monitor
- SAN-30 - Personal CO Safety Monitor

## INDUSTRIES



Beverage



Agriculture



Brewing



Safety



Industrial