

# SprintIR™ Datasheet

## High Speed Carbon Dioxide Sensor

SprintIR is a high speed (20 Hz) CO<sub>2</sub> sensor, ideally suited for applications which require capture of rapidly changing CO<sub>2</sub> concentrations including metabolic assessment and analytical instrumentation.




- High speed sensing (20Hz)
- Measurement ranges from 0 to 100%
- 3.3V supply
- Low power requirement 35mW
- Flow through adaptor (Optional)

### Part Numbers

**GC-0017 20% CO<sub>2</sub>**  
**GC-0018 100% CO<sub>2</sub>**

**CM-0013 Tube Adaptor**  
**(Optional)**



# Specifications

| <b>CO2 Measurement</b>                      |  |
|---|--|
| <b>Sensing Method</b>                       | Non-dispersive infrared (NDIR) absorption<br>Patented Gold-plated optics<br>Patented Solid-state source and detector |
| <b>Sample Method</b>                        | Diffusion(Standard) / Flow through (with flow-through adapter)   |
| <b>Measurement Range</b>                    | 0-5%, 0-20%, 0-60%, 0-100%   |
| <b>Accuracy</b>                             | ±70 ppm +/- 5% of reading <sup>1</sup><br>(100% Range ±300 ppm +/-5% of reading <sup>1</sup> )                       |
| <b>Measurement Noise</b>                    | <10% of reading with no digital filtering  |
| <b>Non Linearity</b>                        | < 1% of FS   |
| <b>Pressure Dependence</b>                  | 0.1% of reading per mbar in normal atmospheric conditions  |
| <b>Operating Pressure Range<sup>2</sup></b> | 950 mbar to 10 bar <sup>3</sup>  |

| <b>General Performance</b>  |   |
|-----------------------------|---|
| <b>Warm-up Time</b>         | < 1 minute  |
| <b>Operating Conditions</b> | 0°C to 50°C (Standard)<br>-25°C to 55°C (Extended range)<br>0 to 95% RH, non-condensing |
| <b>Recommended Storage</b>  | -30°C to +70°C  |


**Note 1:** All measurements are at STP unless otherwise stated.

**Note 2:** Excludes Flow-through adapter. Contact GSS for more information

**Note 3:** External Pressure calibration required.

| Electrical/ Mechanical |   |
|------------------------|---|
| Power Input            | <ul style="list-style-type: none"> <li>• 3.2 to 5V. (3.3V recommended)</li> <li>• Peak current 100mA</li> <li>• Average Current &lt;15mA</li> </ul> |
| Power Consumption      | 35 mW   |
| Output                 | UART only   |

Dimensions and Wiring Connections  
 2x5 0.1" header. Pin 1 is identified on the dimensional drawing.



| Function        | Pin # | Pin # | Function |
|-----------------|-------|-------|----------|
| 0V              | 1     | 2     | N/C      |
| +3.3V           | 3     | 4     | 0V       |
| Sensor Rx (in)  | 5     | 6     | 0V       |
| Sensor Tx (out) | 7     | 8     | Zero N   |
| N/C             | 9     | 10    | Zero Air |

Pin 2 should not be connected. Pins 4 and 6 do not require connection and are internally connected to GND.

The zeroing options are for hardware zeroing (both active low). These functions can also be implemented by sending a serial command (recommended).

Typical connections for digital interface are GND, 3.3V, Rx and Tx. Note that the Vh for the serial Tx line will be 3V regardless of the supply voltage.

This documentation is provided on an as-is basis and no warranty as to its suitability or accuracy for any particular purpose is either made or implied. CO2Meter will not accept any claim for damages howsoever arising as a result of use or failure of this information. Your statutory rights are not affected. This information is not intended for use in any medical appliance, device or system in which the failure of the product might reasonably be expected to result in personal injury. This document provides preliminary information that may be subject to change without notice.